

Chemola™ Desco 1055 is a state-of-the-art synthetic lubricant that is exceedingly resistant to hydrocarbons, water and hydrochloric acid. Chemola™ Desco 1055 is formulated with solid lubricants to provide lubrication to 600°F.

Recommended Uses

Frac applications, condensate, aliphatic hydrocarbons, butane, diesel fuel, hot asphalt, hot gases, hot oil, LPG, natural gas, sour gas and oil. Used worldwide for hydrogen sulfide and carbon dioxide applications.

Typical Characteristics

	Silver-black, smooth, tacky
	1.5 - 2
	280-310
	280-310
	Synthetic ester blend
	10,000 cSt at 40°C
	-15°F (-9°C)
	Inorganic
	Antioxidant package
	Molydisulfide, natural minerals
	>500°F (260°C)
	>450°F (232°C)
	0°F to 600°F (-18°C to 316°C)
	Pass

Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com



South Coast Products
works hard to be environmentally conscious.
As a result, we are proud to offer eco-friendly
products when available. Visit our website for
more details.

ECO
friendly

Chemola™ Desco 1055

Premium Synthetic Valve Lubricant

Packaging Information

Item Number	Unit Size	Quantity
	10 lb can	
	"J" stick 1-3/8" x 8-1/2"	16 per box
	20 lb pail	
	40 lb pail	
	120 lb keg	
	"K" stick 1-1/2" x 10-1/2"	12 per box
	400 lb drum with liner	

Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com



South Coast Products
works hard to be environmentally conscious.
As a result, we are proud to offer eco-friendly
products when available. Visit our website for
more details.

ECO friendly