



Chemola™ Desco 600

Synthetic Valve Lubricant

Chemola™ Desco 600 is a superior lubricant formulated for resistance to hydrocarbons. It contains 100% synthetic fluids with a non-soap thickener. Chemola™ Desco 600 is our most popular lubricant for non-sour services and is formulated for resistance to hydrocarbons, water and synthetic fluids.

Recommended Uses

Chemola™ Desco 600 can be used to purge and lubricate valves after hydrostatic testing. It can be used in aliphatic hydrocarbons, crude distillates, crude oil, diesel fuel, hydrocarbon liquids, kerosene, LPG, lubricating oils and natural gas.

Typical Characteristics

	Brown, smooth, tacky
3	
230-260	
230-260	
Natural and synthetic ester	
800 cSt at 40°C	
5°F (-15°C)	
Inorganic	
Antioxidant package	
1.0	
8.5	
>500°F (260°C)	
>450°F (232°C)	
-20°F to 450°F (-29°C to 232°C)	
0.6 mm	
160 kgf	
Pass	

Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com



South Coast Products
works hard to be environmentally conscious.
As a result, we are proud to offer eco-friendly
products when available. Visit our website for
more details.

ECO
friendly

Chemola™ Desco 600

Synthetic Valve Lubricant

Packaging Information

Item Number	Unit Size	Quantity
	"B" stick 3/8" x 1-1/2"	72 per box
	"C" stick 7/16" x 2-1/8"	32 per box
	"D" stick 1/2" x 2-1/4"	28 per box
	"G" stick 5/8" x 3-1/2"	14 per box
	"J" stick 1-3/8" x 8-1/2"	16 per box
	"K" stick 1-1/2" x 10-1/2"	12 per box
	14 oz cartridge	10 per carton
	10 lb can	
	20 lb pail	
	40 lb pail	
	120 lb keg	
	400 lb drum	

Special packaging sizing available upon request.

SOUTH COAST PRODUCTS

P.O. Box 450109 Houston, Texas 77245 www.socousa.com
Tel: (713) 225-0048 (800) 535-5823 custserv@socousa.com



South Coast Products
works hard to be environmentally conscious.
As a result, we are proud to offer eco-friendly
products when available. Visit our website for
more details.

ECO friendly