



## Chemola™ Desco 625-PAK

Injectable Packing with PTFE and Aramid Fibers

**Chemola™ Desco 625 Pak** is our most popular blend of 100% synthetic base oils with synthetic fibers and fillers that provide a sure seal. The base fluids provide a very low coefficient of expansion (from -80°F to 500°F) while being oil resistant. The solid synthetic fibers and fillers provide a sure seal and are inert to most services.

### Recommended Uses

Chemola™ Desco 625 Pak can be used in hydrocarbons, steam, water, sour gas and sour crude. It is pumpable with a high pressure (10,000 p.s.i.) lubrication hand gun.

### Typical Characteristics

Color	Green, grainy
Viscosity	>6
Base Oil	30-60
Base Type	Synthetic
Viscosity Index	60,000 cSt at 25°C
Temperature Range	-40°F (-40°C)
Material	Synthetic fibers, fillers
Specific Gravity	1.4
Density	11.9
Temperature Rating	>500°F (260°C)
Temperature Rating	>450°F (260°C)
Temperature Range	-80°F to 500°F (-62°C to 260°C)

### Packaging Information

Item Number	Unit Size	Quantity
	"B" stick 3/8" x 1-1/2"	72 per box
	"J" stick 1-3/8" x 8-1/2"	16 per box
	"G" stick 5/8" x 3-1/2"	14 per box
	10 lb	
	40 lb	

*Special packaging sizing available upon request.*