



## Chemola™ Desco TFE-Seal 104

Hydrocarbon Service (Contains PTFE) Sealant

**Chemola™ Desco TFE-Seal 104** is a synthetic lubricant/sealant formulated for general hydrocarbon service. It contains fine PTFE flakes suspended in a hydrocarbon resistant base. TFE-Seal 104 is used for sealing valves with moderate seal wear, and is also suitable for use on threads, gaskets, stuffing boxes and valve stems.

### Recommended Uses

Chemola™ Desco TFE-Seal 104 can be used to seal valves in the following services: Aliphatic hydrocarbons, crude distillates, crude oil, diesel fuel, hydrocarbon liquids, kerosene, LPG and lubricating oils.

### Typical Characteristics

	Blue, grainy, tacky
	1 - 2
	280-320
	280-320
	Natural and synthetic ester
	800 cSt at 40°C
	5°F (-15°C)
	Inorganic
	Antioxidant package
	PTFE
	1.3
	10.6
	>500°F (260°C)
	>500°F (260°C)
	0°F to 450°F (-18°C to 232°C)
	Pass
	Pass
	Pass
	Pass

*Special packaging sizing available upon request.*

# Chemola™ Desco TFE-Seal 104

## Hydrocarbon Service (Contains PTFE) Sealant

### Packaging Information

Item Number	Unit Size	Quantity
	"B" stick 3/8" x 1-1/2"	72 per box
	"C" stick 7/16" x 2-1/8"	32 per box
	"D" stick 1/2" x 2-1/4"	28 per box
	"G" stick 5/8" x 3-1/2"	14 per box
	"J" stick 1-3/8" x 8-1/2"	16 per box
	"K" stick 1-1/2" x 10-1/2"	12 per box
	14 oz cartridge	10 per carton
	10 lb can	
	45 lb pail	

*Special packaging sizing available upon request.*