



Chemola™ ThredOn™ 345 Weather Coat

Protective Coating for Machinery, Tubulars Stored Outside and Pipe Threads

Chemola™ ThredOn™ 345 Weather Coat is a protective coating used in machine shops, pipe yards, offshore platforms or anywhere metal needs to be protected for short or long periods of time. It leaves a semi-fluid, non-hardening coating that protects metal against rust and corrosion for extended periods in sun, rain, sand, salt-water and/or frigid temperatures. Weather Coat can be brushed on or thinned with mineral spirits and sprayed on or used for dip coating. It can be removed using common solvents such as diesel or paint thinner.

Recommended Uses

Excellent for freshly cut metals, drillpipe, equipment and OCTG connections. Chemola ThredOn 345 Weather Coat meets or exceeds all API RP 5A3 and ISO 13678 recommendations and requirements including Annex L.

Typical Characteristics



Reddish-brown, smooth
1
300-330
300-330
Calcium complex
Mineral oil
140 cSt at 40°C
10 cSt at 100°C
-10°F (-23°C)
Corrosion inhibitor antioxidant package
0.9
7.5
>500°F (260°C)
430°F (221°C)

Packaging Information

Item Number	Unit Size
	10 lb pail
	35 lb pail
	400 lb drum

Special packaging sizing available upon request.